



Clavettes parallèles

-Type brut-

Price Reduction

10% en moyenne



Clavettes coniques à talon

Données CAO

RoHS 10 **KET**

JIS B 1301-1996 (nouvelle norme JIS)

Type	Matériau	Résistance à la traction
KET	1.1191/C45E	600N/mm ² ou plus

Réf. pièce	Type	B	Tolérance (h9)	H	Tolérance de H	C	€ Unit Price				
							Qté 1-3	4-19	20-49	50-100	
3	3	0	-0.025	3	0	-0.025	0.16-0.25				
4	4	0	-0.030	4	0	-0.030	0.25-0.40				
5	5	0	-0.030	5	0	-0.030					
6	6	0	-0.036	6	0	-0.036	0.40-0.60				
7	7	0	-0.036	7	0	-0.036					
8	8	0	-0.043	8	0	-0.043	0.40-0.60				
10	10	0	-0.043	10	0	-0.043					
12	12	0	-0.043	12	0	-0.043					
14	14	0	-0.043	14	0	-0.043					
15	15	0	-0.043	15	0	-0.043					
16	16	0	-0.043	16	0	-0.043					
18	18	0	-0.043	18	0	-0.043					



Exemple de commande

Réf. pièce

KET10



Délai de livraison

6 Jours P87

RoHS 10 **KTH**

JIS B 1301-1996 (nouvelle norme JIS)

Type	Matériau	Résistance à la traction
KTH	1.1191/C45E	600N/mm ² ou plus

Réf. pièce	Type	Bh9	H	L	h1	h2 / f (E)	C	€ Unit Price				
								Qté 1-4	5-9	10-29	30-49	
4	4	4	4	30	7	4	4	0.16-0.25				
5	5	0	-0.030	5	0	-0.030	0.25-0.40					
6	6	6	6	45	10	6						
7	7	7.2	0	-0.036	50	7	7	0.40-0.60				
8	8	7	0	-0.036	60	11	7					
10	10	8	0	-0.090	75	12	8	0.60-0.80				
12	12	8	0	-0.090	90	12	8					
14	14	9	0	-0.090	110	14	9	1.00-1.20				
15	15	10.2	0	-0.090	110	15	10					
16	16	10	0	-0.090	120	16	10					
18	18	11	0	-0.110	135	18	11					
20	20	12	0	-0.110	150	20	12					
22	22	14	0	-0.110	170	22	14					
24	24	16.2	0	-0.070	180	24	16	0.60-0.80				
25	25	14	0	-0.110	200	22	14					
28	28	16	0	-0.110	210	25	16					
32	32	18	0	-0.110	240	28	18					
35	35	22.3	0	-0.084	260	32	22	1.00-1.20				
36	36	20	0	-0.130	280	20	36					
38	38	24.3	0	-0.084	285	36	24					



Exemple de commande

Réf. pièce

KTH12



Délai de livraison

8 Jours

Express A 2,00€/pièce P88

Frais de livraison "Express" de 5,40 EUR pour 3 pièces identiques ou plus.

Acier inoxydable **RoHS 10** **KETS**

JIS B 1301-1996 (nouvelle norme JIS)

Type	Matériau	Résistance à la traction
KETS	1.4401/X5CrNiMo17-12-2	600N/mm ² ou plus

Réf. pièce	Type	B	H	C	€ Unit Price						
					Qté 1-3	4-19	20-49	50-100			
2	2	+0.015	-0.025	2	+0.015	-0.025	0.2				
3	3	+0.015	-0.025	3	+0.015	-0.025	0.3				
4	4	+0.015	-0.025	4	+0.015	-0.025					
5	5	+0.015	-0.025	5	+0.015	-0.025	0.5				
6	6	+0.015	-0.025	6	+0.015	-0.025					
7	7	+0.015	-0.025	7	+0.015	-0.025					
8	8	+0.015	-0.025	8	+0.015	-0.025					
10	10	+0.015	-0.025	10	+0.015	-0.025					
12	12	+0.015	-0.025	12	+0.015	-0.025					
14	14	+0.015	-0.025	14	+0.015	-0.025					



Exemple de commande

Réf. pièce - H

KETS8 - 7



Délai de livraison

6 Jours P87



Modifications

Réf. pièce - (LC)

KTH10 - LC60

Modification	Code	Spéc.	Supplément de prix																				
Modification de la dimension L	LC	LC=Incrément de 1mm LC(Min.)≤LC≤L Pour LC(Min.), voir ci-dessous.	2,00																				
		<table border="1"> <thead> <tr> <th>B</th> <th>LC (Min.)</th> </tr> </thead> <tbody> <tr><td>4 - 5</td><td>10</td></tr> <tr><td>6 - 7 - 8</td><td>15</td></tr> <tr><td>10 - 12</td><td>20</td></tr> <tr><td>14 - 15 - 16</td><td>22</td></tr> <tr><td>18 - 20</td><td>25</td></tr> <tr><td>22 - 24 - 25</td><td>30</td></tr> <tr><td>28</td><td>35</td></tr> <tr><td>32 - 35 - 36</td><td>40</td></tr> <tr><td>38</td><td>45</td></tr> </tbody> </table>	B	LC (Min.)	4 - 5	10	6 - 7 - 8	15	10 - 12	20	14 - 15 - 16	22	18 - 20	25	22 - 24 - 25	30	28	35	32 - 35 - 36	40	38	45	
B	LC (Min.)																						
4 - 5	10																						
6 - 7 - 8	15																						
10 - 12	20																						
14 - 15 - 16	22																						
18 - 20	25																						
22 - 24 - 25	30																						
28	35																						
32 - 35 - 36	40																						
38	45																						